



SANDMOVER



THE SANDMOVER IS THE RIGHT MACHINE FOR QUICKLY ADDING A LAYER OF SAND, SPLIT OR GRAVEL TO THE FIELD. IN ADDITION, THE MACHINE IS SUITABLE FOR FILLING (DRAINAGE) TRENCHES BY THE USE OF A HYDRAULICALLY ADJUSTABLE CONVEYOR BELT.



THERE ARE TWO SUBSOILERS LOCATED IN THE BODY, WHICH ASSURE A CONTINUOUS FLOW TO THE DISTRIBUTOR ROLLER. THE FLOW OF SAND IS HYDRAULICALLY TURNED ON AND OFF FROM WITHIN THE TRACTOR, THE THICKNESS OF THE LAYER CAN BE MECHANICALLY SET AT THE BACK OF THE MACHINE.

THE SANDMOVER RESTS ON FOUR BALLOON TIRES, IN ORDER TO AFFECT THE FIELD AS LITTLE AS POSSIBLE, AND THE OUTER WHEELS ARE EQUIPPED WITH HYDRAULIC BRAKES. THE MACHINE IS CONNECTED TO THE TRACTOR BY A ROTATING DRAWBAR EYE, AND THE DRAWBAR IS MECHANICALLY RETRACTABLE, TO SHORTEN THE TRANSPORTATION LENGTH.





SANDMOVER

SM-180

- WORKING WIDTH: 1,8 MTR
- DIMENSIONS DURING OPERATION/TRANSPORT: 4,3x2,5x2,3 /3,1x2,5x2,3 MTR (LXWXH)
- WEIGHT 2550 KG (EXCL. SAND)
- CAPACITY SANDBUNKER: 5 M³ (FLAT FULL)
- POWER REQUIREMENT: > 90 HP
- LINKAGE: DRAWBAR EYE
- 1X DOUBLE ACTING HYDRAULIC VALVE / SAND-DISTRIBUTOR ROLLER (25 L/MIN)
- 1X DOUBLE ACTING HYDRAULIC VALVE / CONTROL SAND DRAIN (25 L/MIN)
- FOUR BALLOON TIRES (15,0/55-17 10 PLY)

OPTIONS:

- RADIAL BALLOON TIRES
- HYDRAULIC BRAKES

SM-250

- WORKING WIDTH: 2,5 MTR
- DIMENSIONS DURING OPERATION/TRANSPORT: 4,3x2,75x2,3 /3,1x2,75x2,3 MTR (LXWXH)
- WEIGHT 2750 KG (EXCL. SAND)
- CAPACITY SANDBUNKER: 6 M³ (FLAT FULL)
- POWER REQUIREMENT: > 90 HP
- LINKAGE: DRAWBAR EYE
- 1X DOUBLE ACTING HYDRAULIC VALVE / SAND-DISTRIBUTOR ROLLER (25 L/MIN)
- 1X DOUBLE ACTING HYDRAULIC VALVE / CONTROL SAND DRAIN (25 L/MIN)
- FOUR BALLOON TIRES (15,0/55-17 10 PLY)

OPTIONS:

- RADIAL BALLOON TIRES
- HYDRAULIC BRAKES

GKB MACHINES
MIDDELWEG 1
2992 SP BARENDRECHT
NEDERLAND

WWW.GKBMACHINES.COM
INFO@GKBMACHINES.COM
TEL.: +31(0)180 64 29 22
FAX: +31(0)180 62 09 23