



# VSTRONG



THE GKB VSTRONG HAS BEEN DEVELOPED, BECAUSE OF INCREASING MARKET DEMAND, FOR AN AGGRESSIVE AERATING MACHINE TO REMOVE THATCH. BY REMOVING THATCH, MOSS AND OTHER MATERIAL THE GRASS IS ALLOWED MORE SPACE TO GROW, PROVIDES PERMEABILITY OF THE TOP LAYER, AND INCREASES RESISTANCE TO DISEASE AND INSECTS. IN ADDITION, THE WATER PERMEABILITY OF THE TOP LAYER IS DRASTICALLY IMPROVED.



THE VSTRONG USES THE COMBI-ROTOR SYSTEM, WHICH CAN BE USED FOR BOTH TOTAL REMOVAL, WITH THE FRASING BLADES, AS WELL AS VERTICUTTING.



THE VSTRONG IS EQUIPPED WITH AN ADJUSTABLE HYDRAULIC TAILGATE TO GUIDE THE OUTPUT OF THE DISPATCHED MATERIAL. THE PLASTIC SCRAPER ON THE ROLLERS ENSURE THAT THE ROLLERS ALWAYS REMAIN CLEAN.







# VSTRONG

## VS-120

- WORKING WIDTH: 1,2 MTR
- WORKING DEPTH: MAX. 5 CM
- WORKING DEPTH VERTICUTTING: MAX. 4 CM (C.D. 2,0 / 4,0 / 6,0 / 8,0 CM)
- DIMENSIONS OPERATION/TRANSPORT: 1,4x1,65x1,0 MTR (LXWXH)
- WEIGHT: 350 KG
- POWERCONSUMPTION: > 40 HP
- LINKAGE: STANDARD 3 POINT CAT II
- 1X DOUBLE ACTING HYDRAULIC VALVE TRANSPORT HOOD (20 L/MIN)

## VS-160

- WORKING WIDTH: 1,6 MTR
- WORKING DEPTH: MAX. 5 CM
- WORKING DEPTH VERTICUTTING: MAX. 4 CM (C.D. 2,5 / 5,0 / 7,5 / 10,0 CM)
- DIMENSIONS OPERATION/TRANSPORT: 1,6x2,05x1,0 MTR (LXWXH)
- WEIGHT: 500 KG
- POWERCONSUMPTION: > 45 HP
- LINKAGE: STANDARD 3 POINT CAT II
- 1X DOUBLE ACTING HYDRAULIC VALVE TRANSPORT HOOD (20 L/MIN)

## VS-200

- WORKING WIDTH: 2,0 MTR
- WORKING DEPTH: MAX. 5 CM
- WORKING DEPTH VERTICUTTING: MAX. 4 CM (C.D. 2,5 / 5,0 / 7,5 / 10,0 CM)
- DIMENSIONS OPERATION/TRANSPORT: 1,7x2,05x1,1 MTR (LXWXH)
- WEIGHT: 750 KG
- POWERCONSUMPTION: > 65 HP
- LINKAGE: STANDARD 3 POINT CAT II
- 1X DOUBLE ACTING HYDRAULIC VALVE TRANSPORT HOOD (20 L/MIN)

## VS-240

- WORKING WIDTH: 2,4 MTR
- WORKING DEPTH: MAX. 5 CM
- WORKING DEPTH VERTICUTTING: MAX. 4 CM (C.D. 2,5 / 5,0 / 7,5 / 10,0 CM)
- DIMENSIONS OPERATION/TRANSPORT: 1,7x2,85x1,1 MTR (LXWXH)
- WEIGHT: 900 KG
- POWERCONSUMPTION: > 90 HP
- LINKAGE: STANDARD 3 POINT CAT II
- 1X DOUBLE ACTING HYDRAULIC VALVE TRANSPORT HOOD (20 L/MIN)

GKB MACHINES  
MIDDELWEG 1  
2992 SP BARENDRECHT  
NEDERLAND

WWW.GKBMACHINES.COM  
INFO@GKBMACHINES.COM  
TEL.: +31(0)180 64 29 22  
FAX: +31(0)180 62 09 23